

Cadre avec arrêt	Cadre enfiguré
<p><b>Cadre avec arrêt</b></p> <p>Dimensions: <math>1 \frac{3}{8}</math>" (stop width), <math>1 \frac{1}{16}</math>" (stop height), <math>\frac{3}{8}</math>" (solid wood veneer thickness), <math>\frac{9}{16}</math>" (solid wood veneer thickness), <math>\frac{3}{8}</math>" (solid wood veneer thickness).</p> <p>Labels: Lisière de bois solide, Arrêt, Placage de bois, Lisière de bois solide.</p> <p>Profondeur standard</p>	<p><b>Cadre enfiguré</b></p> <p>Dimensions: <math>1 \frac{3}{8}</math>" (width), <math>1 \frac{1}{16}</math>" (height), <math>\frac{1}{2}</math>" (solid wood thickness), <math>\frac{9}{16}</math>" (solid wood thickness).</p> <p>Label: Bois solide.</p> <p>Profondeur standard</p>

**Profondeur de cadre standard :** 3-9/16", 4-9/16", 5-9/16", 6-9/16" et 7-9/16".

Astragale de surface	Barrure d'astragale
<p><b>Astragale de surface</b></p> <p>Dimensions: <math>\frac{7}{8}</math>" (width), <math>\frac{1}{2}</math>" (height).</p>	<p><b>Barrure d'astragale</b></p> <p>Dimensions: 7" (length), <math>\frac{3}{4}</math>" (height), <math>\frac{7}{8}</math>" (width).</p>

Barrure à bille	Loquet sur cadre
<p><b>Barrure à bille</b></p> <p>Dimensions: <math>\frac{13}{16}</math>" (width), <math>\frac{9}{16}</math>" (height), <math>\frac{15}{16}</math>" (width), <math>\frac{5}{8}</math>" (height), <math>\frac{7}{8}</math>" (width), <math>\frac{3}{4}</math>" (height), <math>\frac{1}{4}</math>" (height).</p>	<p><b>Loquet sur cadre</b></p> <p>Dimensions: <math>2 \frac{1}{4}</math>" (width), <math>1 \frac{1}{4}</math>" (height), Rayon = <math>\frac{1}{4}</math>" (radius).</p> <p>Label: Position du loquet sur le cadre.</p>